

SPECIFICATION SHEET | KW

Product Name: KLIME-EZEE Extra Wide Range | KW

Safe Working Load (SWL): 300 kg

Product Overview:

The **KLIME-EZEE Extra Wide Range (KW)** is designed for tasks requiring enhanced stability. With its wider framework and steps, this range ensures greater comfort for users, making it ideal for applications that involve handling bulky items or require additional working space. Perfect for warehouses, industrial sites, and environments prioritising safety and ease of access.



Key Features:

- **Extra-Wide Steps:** Enhanced comfort and stability for users.
- **Spacious Platform:** Ideal for working with larger tools or materials.
- **Heavy-Duty Construction:** Built to withstand demanding industrial use.
- **Customisation Options:** Available with six different colour options, two tread types, and endless exit options to meet your specific needs.
- **Ready-to-Use:** Delivered assembled and ready for operation.

Model Variants and Specifications:

Product Code	Treads	Working Platform Height	Work Height	Overall Height	Overall Width	Overall Length	Weight	Brake Type
KW 03	3	750	1750 - 2500	1750	995	820	42	Side brake
KW 04	4	1000	2000 - 2750	2000	995	1040	51	Central brake
KW 05	5	1250	2250 - 3000	2250	995	1270	75	Central brake
KW 06	6	1500	2500 - 3250	2500	995	1360	82	Central brake
KW 07	7	1750	2750 - 3500	2750	995	1450	90	Central brake
KW 08	8	2000	3000 - 3750	3000	995	1575	98	Central brake
KW 09	9	2250	3250 - 4000	3250	995	1730	110	Central brake
KW 10	10	2500	3500 - 4250	3500	1150	1905	118	Central brake
KW 11	11	2750	3750 - 4500	3750	1150	2070	125	Central brake
KW 12	12	3000	4000 - 4750	4000	1150	2230	136	Central brake
KW 13	13	3250	4250 - 5000	4250	1380	2470	145	Central brake
KW 14	14	3500	4500 - 5250	4500	1380	2630	150	Central brake
KW 15	15	3750	4750 - 5500	4750	1470	2795	158	Central brake

Please note: All dimensions are approximate and shown in mm, with weights shown in kg.

Due to our ever-improving environment, we may make enhancements to our products which affect dimensions. Therefore reserve the right to amend these at any time to better serve our customer. To confirm the spec go to : klime-ezee.com/kw.

Technical Details:

- **Angle of ascent:** 60 degree
- **Materials:** Fully welded frame 25mm diameter tube
- **Overall Width:** The main framework is approximately 750 mm (w). The listed width is the maximum point, measured at the axle.
- **Working Platform Size:** Standard platform size is 700 mm (w) x 400 mm (d), with optional extensions available. See our modifications page for customisation options.
- **Tread Dimensions:** Each tread is 700 mm (w) x 200 mm (d), offering secure footing.
- **Platform Toe Plate:** All sizes in this range have rear toe plate, with 7-15 treads having toe plate to all three sides of the platform.
- **Rear Legs:** The rear legs are angled outward at approximately 3 degrees for stability. If a rear exit gate is required, adding "Flush Back Wheels" is recommended for compatibility.

Applications:

The KW range is suitable for various environments where space is limited, including:

- Warehouses
- Maintenance facilities
- Industrial & manufacturing environments

Maintenance Recommendations:

To ensure ongoing safety and performance, a maintenance inspection every six months is recommended. You can visit our website for more information.

Document last updated 22.11.2024