

SPECIFICATION SHEET | KE

Product Name: KLIME-EZEE Industrial Range | KE

Safe Working Load (SWL): 300 kg

Product Overview:

The **KLIME-EZEE Industrial Range (KE)** is engineered for demanding environments, offering unmatched durability and safety. Its sturdy construction ensures long-term reliability while meeting the rigorous requirements of industrial applications. It is ideal for warehouses, factories, and high-traffic environments.



Key Features:

- **Ergonomic Design:** Optimised for safety and ease of use.
- **Comfortable Platform:** Suited for all types of picking, packing and maintenance.
- **Customisable Exit Options:** Optional gate and chained exits.
- **Customisable Colours and Treads:** Available with six different colour options and three tread types.
- **Ready-to-Use:** Fully welded and ready for immediate use upon delivery.

Model Variants and Specifications:

Product Code	Treads	Working Platform Height	Work Height	Overall Height	Overall Width	Overall Length	Weight	Brake Type
KE 03	3	750	1750 - 2500	1750	850	820	26	Side brake
KE 04	4	1000	2000 - 2750	2000	850	1040	30	Central brake
KE 05	5	1250	2250 - 3000	2250	850	1270	44	Central brake
KE 06	6	1500	2500 - 3250	2500	850	1360	52	Central brake
KE 07	7	1750	2750 - 3500	2750	850	1450	60	Central brake
KE 08	8	2000	3000 - 3750	3000	850	1575	73	Central brake
KE 09	9	2250	3250 - 4000	3250	850	1730	77	Central brake
KE 10	10	2500	3500 - 4250	3500	1000	1905	80	Central brake
KE 11	11	2750	3750 - 4500	3750	1000	2070	82	Central brake
KE 12	12	3000	4000 - 4750	4000	1000	2230	86	Central brake
KE 13	13	3250	4250 - 5000	4250	1230	2630	107	Central brake
KE 14	14	3500	4500 - 5250	4500	1230	2630	107	Central brake
KE 15	15	3750	4750 - 5500	4750	1320	2795	109	Central brake

Please note: All dimensions are approximate and shown in mm, with weights shown in kg.

Due to our ever-improving environment, we may make enhancements to our products which affect dimensions. Therefore we reserve the right to amend these at any time to better serve our customers. To confirm the spec go to : klime-ezee.com/ke.

Technical Details:

- **Angle of ascent:** 60 degree
- **Overall Width:** The main framework is approximately 600 mm (w). The listed width is the maximum point, measured at the axle.
- **Working Platform Size:** Standard platform size is 550 mm (w) x 400 mm (d).
- **Tread Dimensions:** Each tread is 550 mm (w) x 200 mm (d), offering secure footing.
- **Platform Toe Plate:** All sizes in this range have rear toe plate, with 7-15 treads having toe plate to all three sides of the platform.
- **Rear Legs:** These splay out from the unit at an approximate 3 degree angle. If you wish to add a rear gate to exit your platform, then you should also consider adding 'Flush Back Wheels'.

Applications:

The KE range is suitable for various environments where space is limited, including:

- Warehouses
 - Factories
 - Industrial settings
-

Maintenance Recommendations:

To ensure ongoing safety and performance, a maintenance inspection every six months is recommended. You can visit our website for more information.

Document last updated 22.11.2024