

SPECIFICATION SHEET | KL

Product Name: KLIME-EZEE Light Weight | KL

Safe Working Load (SWL): 300 kg

Product Overview:

The **KLIME-EZEE Lightweight Range (KL)** is a lighter version of our industrial range. Constructed from high-quality lightweight tube, this range maintains the strength and stability needed for safe operation while being easier to handle and transport. Ideal for lighter-use environments such as retail, offices, and light industrial settings, it combines functionality with convenience, making it perfect for everyday tasks.



Key Features:

- **Lightweight Construction:** Easy to handle and move between tasks.
- **Durable Build:** Fully welded frame made from 19mm diameter tube for durability, supporting a 300 kg load.
- **Non-Slip Treads:** Provide safe and secure footing.
- **Customisation Options:** Available with six different colour options, three tread types, and endless exit options to meet your specific needs.
- **Ready-to-Use:** Delivered assembled and ready for operation.

Model Variants and Specifications:

Product Code	Treads	Working Platform Height	Work Height	Overall Height	Overall Width	Overall Length	Weight	Brake Type
KL 02	2	500	1500 - 2250	1500	650	605	17	Plunger castors
KL 03	3	750	1750 - 2500	1750	650	758	18	Plunger castors
KL 04	4	1000	2000 - 2750	2000	650	911	28	Plunger castors
KL 05	5	1250	2250 - 3000	2250	850	1178	34	Central brake
KL 06	6	1500	2500 - 3250	2500	850	1332	39	Central brake

Please note: All dimensions are approximate and shown in mm, with weights shown in kg.

Due to our ever-improving environment, we may make enhancements to our products which affect dimensions. Therefore reserve the right to amend these at any time to better serve our customer. To confirm the spec go to : klime-ezee.com/kl.

Technical Details:

- **Angle of ascent:** 60 degree
- **Overall Width:** The main framework is approximately 600 mm (w). The listed width is the maximum point, measured at the axle.
- **Working Platform Size:** Standard platform size is 550 mm (w) x 400 mm (d), with optional extensions available. See our modifications page for customisation options.
- **Tread Dimensions:** Each tread is 550 mm (w) x 200 mm (d), offering secure footing.
- **Platform Toe Plate:** All models in this range have rear toe plate on the platform to enhance safety and prevent slips.
- **Rear Legs:** The rear legs are angled outward at approximately 3 degrees for stability. If a rear exit gate is required, adding "Flush Back Wheels" is recommended for compatibility.

Applications:

The KL range is suitable for various environments where space is limited, including:

- Retail
 - Light industrial settings
 - Office environments
-

Maintenance Recommendations:

To ensure ongoing safety and performance, a maintenance inspection every six months is recommended. You can visit our website for more information.

Document last updated 22.11.2024