

## SPECIFICATION SHEET | KNA

**Product Name:** KLIME-EZEE Narrow Aisle Pro Range | KNA

**Safe Working Load (SWL):** 300 kg

### Product Overview:

The **KLIME-EZEE Narrow Aisle Pro Range (KNA)** is designed for use within confined spaces like warehouse aisles, archives and office environments. The step is fully welded and ready for immediate use, with customisable options for colour, tread type, and exit configurations.



### Key Features:

- **Space-Saving Design:** Ideal for narrow spaces, manoeuvrable in tight areas.
- **Robust Construction:** Fully welded frame made from 19mm diameter tube for durability, supporting a 300 kg load.
- **Customisation Options:** Available with six different colour options, three tread types, and endless exit options to meet your specific needs.
- **Ready-to-Use:** Delivered assembled and ready for operation.

### Model Variants and Specifications:

| Product Code | Treads | Working Platform Height | Work Height | Overall Height | Overall Width | Overall Length | Weight | Brake Type      |
|--------------|--------|-------------------------|-------------|----------------|---------------|----------------|--------|-----------------|
| KNA 02       | 2      | 500                     | 1500 - 2250 | 1500           | 590           | 582            | 11     | Plunger castors |
| KNA 03       | 3      | 750                     | 1750 - 2500 | 1750           | 590           | 735            | 19     | Plunger castors |
| KNA 04       | 4      | 1000                    | 2000 - 2750 | 2000           | 590           | 920            | 27     | Plunger castors |
| KNA 05       | 5      | 1250                    | 2250 - 3000 | 2250           | 630           | 1150           | 36     | Central brake   |
| KNA 06       | 6      | 1500                    | 2500 - 3250 | 2500           | 630           | 1360           | 50     | Central brake   |
| KNA 07       | 7      | 1750                    | 2750 - 3500 | 2750           | 630           | 1510           | 51     | Central brake   |
| KNA 08       | 8      | 2000                    | 3000 - 3750 | 3000           | 630           | 1580           | 54     | Central brake   |

**Please note:** All dimensions are approximate and shown in mm, with weights shown in kg.

Due to our ever-improving environment, we may make enhancements to our products which affect dimensions. Therefore reserve the right to amend these at any time to better serve our customer. To confirm the spec go to : [klime-ezee.com/kna](https://klime-ezee.com/kna).

### Technical Details:

- **Angle of ascent:** 60 degree
- **Overall Width:** The main framework is approximately 500 mm (w). The listed width is the maximum point, measured at the axle.
- **Working Platform Size:** Standard platform size is 450 mm (w) x 400 mm (d), with optional extensions available. See our modifications page for customisation options.
- **Tread Dimensions:** Each tread is 450 mm (w) x 200 mm (d), offering secure footing.
- **Platform Toe Plate:** All models in this range feature a three-sided toe plate on the platform to enhance safety and prevent slips.
- **Rear Legs:** The rear legs are angled outward at approximately 3 degrees for stability. If a rear exit gate is required, adding "Flush Back Wheels" is recommended for compatibility.

### Applications:

The KNA range is suitable for various environments where space is limited, including:

- Warehouses
  - Archival storage rooms
  - Office environments
  - Libraries
- 

### Maintenance Recommendations:

To ensure ongoing safety and performance, a maintenance inspection every six months is recommended. You can visit our website for more information.

Document last updated 22.11.2024